

ITMEDIASign100

Professional Digital Signage Player





Key Features

- Mono FullHD
- 1920 × 1080
- Arm[®] Mali™-T860 MP4 GPU
- ASUS Rockchip RK3399
- 16 GB eMMC memory
- WPITCOM Signage Suite 3
 Solution pre-installed
- Compact Entry Model

Display Information

Model ITMediaSign100
Video content 1 x FullHD 1920x1080

GPIO 40 Pin internal
Screen output Vertical or horizontal
Digital Signage Compact basic model

Other Fanless, Low Power Consumption

INTERFACE

Input HDMI 1.3 x 1 CEC Enabled / Mini

HDMI Adapter

SD Card / GPIO / USB 3.2 Gen 1 A x 3,

USB 3.2 Gen1 Type-C® OTG

Networks RTL8211F-CG GbE LAN 10/10/1000 WLAN / WiFi 1 x M.2 - 802.11 a/b/q/n/ac wireless &

BT 5.0 (2T2R)

Audio 2.5mm Microphone + Speaker

Connector

POWER

Power supply 12-19V DC power input

Power consumption (Typ.) ≤ 30W max

Typical: Suspend 0.44W, Burn-in 8.8W, Max.

29,18W (may vary on usage case)

RTC Battery CR2032

ENVIRONMENT

Operation temperature 0°C ~ 60°C

Operation humidity 0% ~ 85% (Non condensing)

SPECIFICATIONS

Physical

Graphics Arm® Mali™-T860 MP4 GPU
Processor ASUS Rockchip RK3399

Memory Integrated 16 GB eMMC memory

RAM Dual-CH LPDDR4 2GB

Color / Housing Black. Metall

Operating systems Debian 11, Android 11

Hyundai ITMC is a registered trademark of ITMediaConsult AG. All other trademarks are the property of their respective manufacturers. We reserve the right to make changes and errors.

Please update your existing product information before placing your order. This product information does not constitute a performance guarantee.

Master imaging, setup & customizing, individual lasering with company names and inventory numbering on request, customer-specific hardware adaptation possible for bulk purchases.

All systems have the necessary certifications required in the EU.

Specifications may be changed without prior notice. Please update your specification before purchasing the product.

Rev 1 - 2023/09/01





https://itmediaconsult.de

